

I hereby certify that this correspondence is being deposited with the United States Postal Service as Express Mail in an envelope addressed to:

ASSISTANT COMMISSIONER OF PATENTS
2900 Crystal Drive
Arlington, VA 22202 - 3513

bearing Label Number EL 057 650 414 and mailed November 30, 2001

Ira Richardson

Print Name

Ira Richardson
Signature

Patent

Inventor(s): David C. Challener and Steven D. Goodman

METHOD OF CREATING PASSWORD LIST FOR REMOTE AUTHENTICATION TO SERVICES

FIELD OF THE INVENTION

The present invention relates to security in computer networks, and more particularly to protecting remote user access in the computer networks.

5 BACKGROUND OF THE INVENTION

Currently, to remotely access a computer network, a user must have a User ID and a password. Typically, a server in the computer network stores the user ID and password in a table. Figure 1 illustrates a conventional user ID and password table. The table 100 comprises a User ID list 102 and a Hash of Password list 104. The Hash of Password list 104 contains a hash
10 of the passwords corresponding to each user ID. When the user logs into the server, the user provides his/her User ID and password. The server hashes the password provided by the user,

and looks up the user's ID in the User ID list 102 in the table 100. The server then compares the stored hashed password corresponding to the user's ID in the Hash of Password list 104 with the hash of the password provided by the user. If they match, then access is granted to the user. If not, then access is denied. By storing the hashes of passwords, the list of passwords cannot be discovered by examining the table.

However, passwords are prone to brute force attacks, such as "dictionary attacks" where an attacker systematically tries known words as passwords. This is a particular security risk especially since most users do not select strong passwords. Also, an attacker can attack "offline", i.e., with another computer. For example, a table of hashes of the most popular passwords can be prepared on another computer. This table may then be used with the server in an attempt to find a match with a user ID in the table 100.

Accordingly, there exists a need for a method and system for improved security in password-based access to computer networks. The method and system should increase the security of the computer network. The present invention addresses this need.

SUMMARY OF THE INVENTION

A method for providing security in password-based access to computer networks, the network including a server and a remote user, includes: signing a phrase by a security chip of the server using an encryption key; associating the signed phrase with the remote user; signing the phrase with an encryption key obtained by the security chip when a request for access to the computer network is received from the remote user; comparing the phrase signed with the

obtained encryption key with the signed phrase associated with the remote user; and granting access to the remote user if the phrase signed with the obtained encryption key is the same as the stored signed phrase associated with the remote user. The use of the encryption key protects against "dictionary attacks". Use of the security chip protects against offline attacks. These

5 provide greater security for the computer network.

BRIEF DESCRIPTION OF THE FIGURES

Figure 1 illustrates a conventional user ID and password table.

Figure 2 illustrates a preferred embodiment of a system with improved security in

10 password-based access to computer networks.

Figure 3 is a flowchart illustrating a method for improved security in password-based access to computer networks.

Figure 4 is a flowchart illustrating a first preferred embodiment of the method for improved security in password-based access to computer networks.

Figure 5 illustrates a security chip key chain.

15

Figure 6 is a flowchart illustrating a second preferred embodiment of the method for improved security in password-based access to computer networks.

DETAILED DESCRIPTION

The present invention provides a method and system for improved security in password-based access to computer networks. The following description is presented to enable one of
5 ordinary skill in the art to make and use the invention and is provided in the context of a patent application and its requirements. Various modifications to the preferred embodiment will be readily apparent to those skilled in the art and the generic principles herein may be applied to other embodiments. Thus, the present invention is not intended to be limited to the embodiment shown but is to be accorded the widest scope consistent with the principles and features
10 described herein.

The method and system in accordance with the present invention comprises a security chip, such as a Trusted Platform Module (TPM). A phrase is signed by the security chip using an encryption key assigned either to the remote user or the security chip. This signed phrase is associated with the remote user and stored. To gain access to the computer network, the
15 encryption key is loaded and used to demonstrate an ability to either recreate the signed phrase or to decrypt the signed phrase by the security chip. If the demonstration is successful, then access is granted. Otherwise, access is denied. The use of the encryption key protects against "dictionary attacks". Use of the security chip protects against offline attacks. These provide greater security for the computer network.

20 To more particularly describe the features of the present invention, please refer to Figures 2 through 7 in conjunction with the discussion below.

with the obtained encryption key, via step 310. The phrase can be a known phrase or a secret phrase. The phrase signed with the obtained encryption key is then compared with the stored signed phrase associated with the remote user 214, via step 312. If the stored signed phrase is the same as the phrase signed with the obtained encryption key, via step 314, then access is granted to the remote user 214, via step 316. If not, then access is denied, via step 318.

The encryption key provides greater entropy. Thus, it is significantly less prone to brute force attacks than passwords. Many security chips 204, such as the TPM, allow a certain number of unsuccessful password entries before locking out a remote user. Thus, using a security chip further decreases the exposure to brute force attacks. Also, because the cooperation of the security chip 204 is required to gain access, offline attacks are not possible.

Figure 4 is a flowchart illustrating a first preferred embodiment of the method for improved security in password-based access to computer networks. First, a public key/private key pair is created for the remote user 214 by the security chip 204, via step 402. Public key/private key pair cryptography is well known in the art. The remote user's 214 public/private key pair is stored in the security chip's 204 key chain. Figure 5 illustrates a security chip key chain. The security chip 204 generates a set of grandfather public/private key pairs 502 for the computer network. Each of these grandparent key pairs 502 is wrapped using the security chip's 204 public key 206. The security chip 204 can then generate parent key pairs 504 and wrap them in the grandparent key's 502 public key. Child key pairs 506 may be generated and wrapped in the parent key's 504 public key. The private key created for the remote user 214 by the security chip 204 is stored in such a key chain.

must attack the server 202, which has the security chip 204. In addition, security chips 204 such as the TPM allow only a certain number of unsuccessful entries of a password before a user is locked out. So the use of the security chip 204 enforces protection against hardware hammering.

Figure 6 is a flowchart illustrating a second preferred embodiment of the method for improved security in password-based access to computer networks. First, a password for the remote user 214 is signed by the security chip 204 with the security chip's 204 private key 208, via step 602. The signed password is associated with the remote user 214 and stored on the server 202, via step 604, in a user ID/signed password table similar to table 100 illustrated in Fig. 1, except a list of signed passwords associated with each user ID is stored in place of the Hash of Password list 104. When the server 202 receives a password from the remote user 214, via step 606, the server 202 sends the received password to the security chip 204, via step 608. The security chip 204 then loads its private key 208, via step 610, and signs the received password with it, via step 612. The received password signed with the security chip's 204 private key 208 is then compared with the stored signed password associated with the remote user 214, via step 614. If they match, via step 616, then access is granted to the remote user 214, via step 618. If not, then access is denied, via step 620.

In the second preferred embodiment, additional entropy is provided because the cooperation of the security chip 204 is required. Thus, offline attacks are not possible. However, the public key 206 of the security chip 204 should be destroyed or hidden to avoid inversion of the stored signed passwords by an attacker.

Figure 7 is a flowchart illustrating a third preferred embodiment of the method for improved security in password-based access to computer networks. First, a blob is created for the remote user 214, via step 602, where the blob comprises the remote user's 214 password signed with the security chip's 204 private key 208. The blob is associated with the remote user 214 and stored on the server 202, via step 604, in a user ID/hashed password/blob table similar to the table 100 illustrating in Fig. 1, except an additional column for the blobs associated with each user ID is added. When the server 202 receives a password from the remote user 214, via step 606, the received password and the blob associated with the remote user's user ID are sent to the security chip 204, via step 608. The security chip 204 then decrypts the blob using its public key 206 to obtain the password stored in the blob, via step 610. The stored password is then compared with the received password, via step 612. If they match, via step 614, then the access is granted to the remote user 214, via step 616. Otherwise, access is denied, via step 618.

Because the cooperation of the security chip 204 is required in the third embodiment, only a certain number of unsuccessful entries of the password are allowed. This provides additional entropy by protecting against hardware hammering.

A method and system for improved security in password-based access to computer networks has been disclosed. The system comprises a security chip, such as a Trusted Platform Module (TPM). A phrase is signed by the security chip using an encryption key assigned either to the remote user or the security chip. This signed phrase is associated with the remote user and stored. To gain access to the computer network, the encryption key is loaded and used to demonstrate an ability to either recreate the signed phrase or to decrypt the signed phrase by the

security chip. If the demonstration is successful, then access is granted. Otherwise, access is denied. The use of the encryption key protects against "dictionary attacks". Use of the security chip protects against offline attacks. These provide greater security for the computer network.

Although the present invention has been described in accordance with the embodiments
5 shown, one of ordinary skill in the art will readily recognize that there could be variations to the embodiments and those variations would be within the spirit and scope of the present invention. Accordingly, many modifications may be made by one of ordinary skill in the art without departing from the spirit and scope of the appended claims.

For reference